

WINTER GLOVES

GLOVES - Ref. GA06 - Size: 8 to 11

EN ISO 21420:2020 + A1:2024

EN 388:2016 + A1:2018 level 4141X



The PPE Specialist

PRODUCT PHOTOS



UNISEX MODEL

3M
Thinsulate
INSULATION

GO^{RE}
WINDSTOPPER
PRODUCTS

DESCRIPTION

The WINTER 2.0 glove is a special winter handiwork glove. Full of innovation with its 3-layers laminated fabric back, anti-abrasion, anti-slip silicone print, anti-vibration foam as well as its smartphone compatible index fingerprint.

3 MAIN BENEFITS

- **Thinsulate® lining:** synthetic fiber for thermal insulation.
- **Laminated 3-layer fabric:**
first layer: velvet comfort
second layer: Windstopper® (GORE®) breathable/waterproof
third layer: polyester HD Ripstop® fabric.
- **Reinforced** Thumb, palm and knuckles to maintain dexterity.

CARE

Wipe with a dry cloth. Do not wash in washing machine. Store in a dry, ventilated place away from dust and moisture.

VARIANTS

Available in specials « summer » and « all season ».

Reference : GA07 / GA08.

PACKAGING

Boxes of 50 pairs.
Sub-packaging: 5 pairs.
Single-unit packaging.



WINTER GLOVES

GLOVES - Ref. GA06 - Size: 8 to 11

EN ISO 21420:2020 + A1:2024

EN 388:2016 + A1:2018 level 4141X

For resellers,
order on B2B



TECHNICAL SPECS

Reinforced knuckles

Laminated 3-layer fabric

Thinsulate® lining

Neoprene auto-grip and dirt-repellent hook and loop fastener

Silicone prints anti-abrasion and anti-slip

Smartphone compatible fabric

Palm reinforcement and anti-vibration foam

Pre-formed thumb with reinforcements

Anti transpirant sponge fabric

Carabiner hole

GENERAL REQUIREMENTS EN ISO 2142



General requirements relating to glove design and construction, safety, comfort and dexterity, as well as marking and information provided by the manufacturer applicable to all protective gloves.

MECHANICAL RISKS EN 388



Abrasion (number of cycles required for the abrasive paper to pass through the fabric or leather). Level 1 to 4.



Cut resistance EN 388: 2003 (index - compared to a standardized fabric at constant pressure and speed, the number of cycles with a circular blade to cut the material). Level 1 to 5.



Tear resistance (force required in Newtons to tear the material). Level from 1 to 4.



Perforation (force required in Newtons for a punch to pass through the glove). Level 1 to 4.

COMPLIANCE



0598/PPE/25/4510 Issue 1
Issued by notified body 0598

PPE Cat. II

ADDITIONAL TESTS EN 388



ISO 13997 **cut** (force required in Newtons for a razor blade to cut through the material over a 20 mm distance). Level from 0 to F. Test not performed = X.



Impact (maintaining the integrity of the glove following a drop of 2.5 kg with an energy of 5 joules). Success = P.

RESULTS

The GA06 glove is certified
level 4141X



SOLIDUR SAS

335, Impasse Teractive Ouest - ZA Teractive - 50140 Romagny-Fontenay, FRANCE
Tel. +33 (0)2 33 59 45 12



www.solidur.fr



GA06 - UPDATE: 10/2025

