

## AIRPRO GLOVES

GLOVES - Ref. GA07 - Size: 7 to 12

EN ISO 21420:2020 + A1:2024

EN 388:2016 + A1:2018 level 4141X



*The PPE Specialist*

### PRODUCT PHOTOS

### UNISEX MODEL



### DESCRIPTION

The AIRPRO 2.0 Glove is a special summer handiwork glove. Full of innovation with its laminated silicone, anti-abrasion, anti-slip silicone print, anti-vibration foam as well as its smartphone compatible index fingerprint. It has optimal breathability thanks to its stretchable nylon mesh back.

### 3 MAIN BENEFITS

- **3D mesh elastic nylon back:** Sweat evacuating fabric.
- **Materials:** Palm (**60% polyurethane, 40% Nylon®**) and thumb (**5% sponge fabric**)
- **Thumb, palm and knuckle reinforcement** that allow maximum dexterity.

### CARE

Wipe with a dry cloth. Do not wash in washing machine. Store in a dry, ventilated place away from dust and moisture.

### VARIANTS

Available in specials « winter » et « all season ».

Reference: **GA06 / GA08.**

### PACKAGING

Boxes of 100.

Sub-packaging: 5.

Single-unit packaging.



# AIRPRO GLOVES

GLOVES - Ref. GA07 - Size: 7 to 12

EN ISO 21420:2020 + A1:2024

EN 388:2016 + A1:2018 level 4141X

For resellers,  
order on B2B



## TECHNICAL SPECS

Reinforced Knuckle

Silicone prints  
anti-abrasion and anti-slip

Smartphone compatible  
index finger

Palm reinforcement

Preformed reinforced  
thumb

Elastic breathable  
3D mesh

Anti transpirant  
sponge fabric

Auto-grip and dirtrepellent  
hook and loop fastener

Carabiner hole

## GENERAL REQUIREMENTS EN ISO 2142



General requirements relating to glove design and construction, safety, comfort and dexterity, as well as marking and information provided by the manufacturer applicable to all protective gloves.

## COMPLIANCE



0598/PPE/25/4510 Issue 1  
Issued by notified body 0598

PPE Cat. II

## MECHANICAL RISKS EN 388



**Abrasion** (number of cycles required for the abrasive paper to pass through the fabric or leather). Level 1 to 4.



**Cut resistance** EN 388: 2003 (index - compared to a standardized fabric at constant pressure and speed, the number of cycles with a circular blade to cut the material). Level 1 to 5.



**Tear resistance** (force required in Newtons to tear the material). Level from 1 to 4.



**Perforation** (force required in Newtons for a punch to pass through the glove). Level 1 to 4.

## ADDITIONAL TESTS EN 388



ISO 13997 **cut** (force required in Newtons for a razor blade to cut through the material over a 20 mm distance). Level from 0 to F. Test not performed = X.



**Impact** (maintaining the integrity of the glove following a drop of 2.5 kg with an energy of 5 joules). Success = P.

## RESULTS

The GA07 glove is certified  
level 4141X



### SOLIDUR SAS

335, Impasse Teractive Ouest - ZA Teractive - 50140 Romagny-Fontenay, FRANCE  
Tel. +33 (0)2 33 59 45 12

[www.solidur.fr](http://www.solidur.fr) @solidur1946

